



Test Report No.: W7L-P23120016SA01



RADIO TEST REPORT (EN 62311)

Applicant:	Particle Industries, Inc
Address:	325 9th Street, San Francisco, CA 94103, United States Of America

Manufacturer or Supplier:	Particle Industries, Inc
Address:	325 9th Street, San Francisco, CA 94103, United States Of America
Product:	M SoM
Brand Name:	Particle
Model Name:	M524
Date of tests:	Dec. 27, 2023 ~ Feb. 23, 2024

The tests have been carried out according to the requirements of the following standard:

EN IEC 62311:2020

CONCLUSION: The submitted sample was found to COMPLY with the test requirement

Prepared by Jerry Chen Engineer / Mobile Department	Approved by Luke Lu Manager / Mobile Department
Date: Feb. 27, 2024	Date: Feb. 27, 2024

This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.



Test Report No.: W7L-P23120016SA01

TABLE OF CONTENTS

RELEASE CONTROL RECORD	3
1 GENERAL INFORMATION	4
1.1 GENERAL DESCRIPTION OF EUT	4
2 RF EXPOSURE MEASUREMENT	5
2.1 INTRODUCTION	5
2.2 LIMIT	5
2.3 CLASSIFICATION OF THE ASSESSMENT METHODS	7
2.4 TEST RESULTS	8
2.5 CONCLUSION	10



Test Report No.: W7L-P23120016SA01

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
W7L-P23120016SA01	Original release	Feb. 27, 2024



1 GENERAL INFORMATION

1.1 GENERAL DESCRIPTION OF EUT

PRODUCT	M SoM	
BRAND NAME	Particle	
MODEL NAME	M524	
NOMINAL VOLTAGE	VCC: 3.8V. 3V3:3.3V	
MODULATION TYPE	BT_LE	GFSK
	WLAN	DSSS, OFDM
	GPS/GALILEO/GLONASS/BDS	BPSK
	GSM/GPRS/EDGE	GMSK, 8PSK
	WCDMA	BPSK/QPSK
	LTE	QPSK/16QAM
OPERATING FREQUENCY	WLAN	2412 ~ 2472MHz for 11b/g/n(HT20/HT40) 5180 ~ 5240MHz, 5260 ~ 5320MHz, 5500 ~ 5700MHz, 5745 ~ 5825MHz for 11a/ n(HT20) / n(HT40)
	BT_LE	2402MHz ~ 2480MHz
	GPS/GALILEO/GLONASS/BDS	1559MHz ~ 1610MHz
	GSM	880.2MHz ~ 914.8MHz (FOR GSM 900) 1710.2MHz ~ 1784.8MHz (FOR DCS 1800)
	WCDMA	1922.4MHz~ 1977.6MHz (FOR WCDMA Band 1) 882.4MHz ~ 912.6MHz (FOR WCDMA Band 8)
	LTE	1922.5MHz~ 1977.5MHz (FOR LTE Band1) 1710.7MHz ~ 1784.3MHz (FOR LTE Band3) 2502.5MHz~ 2567.5MHz (FOR LTE Band7) 880.7MHz ~ 914.3MHz (FOR LTE Band8) 834.5MHz~ 859.5MHz (FOR LTE Band20) 704.5MHz ~ 746.5MHz (FOR LTE Band28)
HW VERSION	V0.2	
SW VERSION	EG91EXGAR08A14M1G	
I/O PORTS	Refer to user's manual	
CABLE SUPPLIED	N/A	



**BUREAU
VERITAS**

Test Report No.: W7L-P23120016SA01

NOTE:

1. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
2. For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.

2 RF EXPOSURE MEASUREMENT

2.1 INTRODUCTION

This International Standard applies to electronic and electrical equipment for which no dedicated product- or product family standard regarding human exposure to electromagnetic fields applies.

The frequency range covered is 0 Hz to 300 GHz.

The object of this generic standard is to provide assessment methods and criteria to evaluate such equipment against basic restrictions or reference levels on exposure of the general public related to electric, magnetic and electromagnetic fields and induced and contact current.

2.2 LIMIT

The table of the reference field levels shown as below is given in Annex III of the Council Recommendation 1999/519/EC.

**Reference levels for electric, magnetic and electromagnetic fields
(0 Hz to 300 GHz, unperturbed rms values)**

Frequency range	E-field strength (V/m)	H-field strength (A/m)	B-field (μT)	Equivalent plane wave power density S_{eq} (W/m ²)
0-1 Hz	—	$3,2 \times 10^4$	4×10^4	—
1-8 Hz	10 000	$3,2 \times 10^4/f^2$	$4 \times 10^4/f^2$	—
8-25 Hz	10 000	$4\,000/f$	$5\,000/f$	—
0,025-0,8 kHz	$250/f$	$4/f$	$5/f$	—
0,8-3 kHz	$250/f$	5	6,25	—
3-150 kHz	87	5	6,25	—
0,15-1 MHz	87	$0,73/f$	$0,92/f$	—
1-10 MHz	$87/f^{1/2}$	$0,73/f$	$0,92/f$	—
10-400 MHz	28	0,073	0,092	2
400-2 000 MHz	$1,375 f^{1/2}$	$0,0037 f^{1/2}$	$0,0046 f^{1/2}$	$f/200$
2-300 GHz	61	0,16	0,20	10

Notes

1. f as indicated in the frequency range column.
2. For frequencies between 100 kHz and 10 GHz, S_{eq} , E^2 , H^2 , and B^2 are to be averaged over any six-minute period.
3. For frequencies exceeding 10 GHz, S_{eq} , E^2 , H^2 , and B^2 are to be averaged over any $68/f^{1.05}$ -minute period (f in GHz).
4. No E-field value is provided for frequencies < 1 Hz, which are effectively static electric fields. For most people the annoying perception of surface electric charges will not occur at field strengths less than 25 kV/m. Spark discharges causing stress or annoyance should be avoided.

2.3 CLASSIFICATION OF THE ASSESSMENT METHODS

The antenna of the product, under normal use condition is at least 20 cm away from the body of the user. Warning statement to the user for keeping at least 20cm separation distance and the prohibition of operating to a person has been printed on the WWAN easy install sheet. So, this product under normal use is located on electromagnetic far field between the human body.

$$E = \eta_0 H = \frac{\sqrt{30PG(\theta, \phi)}}{r}$$

Far Field Calculation Formula

G = antenna gain relative to an isotropic antenna
 θ, ϕ = elevation and azimuth angles to point of investigation
r = distance from observation point to the antenna
 η_0 = Characteristic impedance of free space



2.4 TEST RESULTS

CALCULATION FOR MAXIMUM E.I.R.P

BLUETOOTH

OPERATING BAND(MHz)	Frequency (MHz)	Antenna Gain (dBi)	Tune-up Conducted Power (dBm)	Output Power E.I.R.P. (dBm)	Output Power E.I.R.P. (mW)	E-Field Strength (V/m)	E-Field Strength Limit (V/m)	E-Field Strength/ Limit	PASS / FAIL
Bluetooth LE	2402	3	6.5	9.50	8.91	2.59	61	0.042	PASS

2.4G WIFI

OPERATING BAND(MHz)	Frequency (MHz)	Antenna Gain (dBi)	Tune-up Conducted Power (dBm)	Output Power E.I.R.P. (dBm)	Output Power E.I.R.P. (mW)	E-Field Strength (V/m)	E-Field Strength Limit (V/m)	E-Field Strength/ Limit	PASS / FAIL
2.4G	2412	3	17.0	20.00	100.00	8.66	61	0.142	PASS

5G WIFI

OPERATING BAND(MHz)	Frequency (MHz)	Antenna Gain (dBi)	Tune-up Conducted Power (dBm)	Output Power E.I.R.P. (dBm)	Output Power E.I.R.P. (mW)	E-Field Strength (V/m)	E-Field Strength Limit (V/m)	E-Field Strength/ Limit	PASS / FAIL
Band 1	5180	6.8	12.0	18.80	75.86	7.54	61	0.124	PASS
Band 2	5260	6.8	12.0	18.80	75.86	7.54	62	0.122	PASS
Band 3	5500	6.8	12.5	19.30	85.11	7.99	63	0.127	PASS
Band 4	5475	6.8	7.0	13.80	23.99	4.24	64	0.066	PASS

GSM

OPERATING BAND(MHz)	Frequency (MHz)	Antenna Gain (dBi)	Tune- up Conduct ed Power (dBm)	Tune- up Conduct ed AV Power (dBm)	Tune- up Conduct ed AV Power (mw)	E-Field Strength (V/m)	E-Field Strength Limit (V/m)	E-Field Strength/ Limit	PASS / FAIL
GSM 900	880.2	2.8	35.0	25.97	395.37	23.77	40.79	0.583	PASS
PCS 1800	1710.2	5.3	32.0	22.97	198.15	22.44	56.86	0.395	PASS

WCDMA

OPERATING BAND(MHz)	Frequency (MHz)	Antenna Gain (dBi)	Tune- up Conduct ed Power (dBm)	Output Power E.I.R.P. (dBm)	Output Power E.I.R.P. (mW)	E-Field Strength (V/m)	E-Field Strength Limit (V/m)	E-Field Strength/ Limit	PASS / FAIL
WCDMA Band I	1922.4	5.3	25.0	30.30	1071.52	28.35	60.29	0.470	PASS
WCDMA Band VIII	882.4	2.8	25.0	27.80	602.56	21.26	40.84	0.521	PASS

LTE

OPERATING BAND(MHz)	Frequency (MHz)	Antenna Gain (dBi)	Tune-up Conduct ed Power (dBm)	Output Power E.I.R.P. (dBm)	Output Power E.I.R.P. (mW)	E-Field Strength (V/m)	E-Field Strength Limit (V/m)	E-Field Strength/ Limit	PASS / FAIL
Band 1	1922.5	5.3	25.0	30.30	1071.52	28.35	60.29	0.470	PASS
Band 3	1710.7	5.3	25.0	30.30	1071.52	28.35	56.87	0.498	PASS
Band 7	2502.5	5.3	25.0	30.30	1071.52	28.35	61	0.465	PASS
Band 8	880.7	2.8	25.0	27.80	602.56	21.26	40.81	0.521	PASS
Band 20	834.5	2.8	25.0	27.80	602.56	21.26	39.72	0.535	PASS
Band 28	704.5	2.8	25.0	27.80	602.56	21.26	36.5	0.582	PASS

COLLOCATED EXPOSURE FIELD STRENGTHS CALCULATION

Band	Frequency (MHz)	(E-Field Strength)/ (Limit)	$\Sigma((\text{E-Field Strength })/ (\text{Limit}))$ of	PASS / FAIL
BT-LE	2402	0.042	0.767	PASS
WLAN	2412	0.142		
WWAN	880.2	0.583		

Note:

Simultaneous Transmitter requirements: $\Sigma ((\text{E-Field Strength })/ (\text{Limit})) \leq 1$

2.5 CONCLUSION

According to Council Recommendation 1999/519/EC and RED (Directive2014/53/EU), the RF exposure analysis concludes that the RF Exposure is CE compliant.

--END--